

Nuvo-9531 series

Compact & fanless Box PC with Intel® Core™ i9/ i7/ i5/ i3 13th/12th Gen.

Features

- > Intel® 13th/12th-Gen Core® 35W/&5W LGA 1700 CPU
- > 4x 2.5GbE with optional PoE+
- > 4x USB 3.2 Gen 1 with screw-lock
- > 212 x 165 x 63mm low-profile design
- > M.2 2280 Gen4x4 NVMe
- > 1x hot-swappable HDD tray for storage
- > Wide temperature operation (-25°C to 60°C)

BRANDNEW



Optional ignition power control



VGA and DP dual display outputs



Rugged and fanless operation

Rich I/O option & outstanding performance

Nuvo-9531 is one of the most compact fanless embedded computers based on the Intel® 13th/12th-Gen platform. Measuring just 212 x 165 x 63 mm, it can fit into restricted spaces, such as in robotic arm and AMR applications. Despite its compact size, Nuvo-9531 does not compromise on performance. Built on the advanced Intel 7 process, Intel® 13th-Gen processors have up to 24 cores/ 32 threads to deliver up to 2x the performance when compared to previous Intel® 10th or 11th-Gen platforms.

Nuvo-9531 has rich I/O functions. It features four 2.5GbE with optional PoE+ PSE and four USB3.2 Gen1 ports for multiple camera connectivity for machine vision and surveillance applications. In addition, it features a Gen4 x4 M.2 NVMe slot for the latest NVMe SSD that supports read/ write speeds up to 7000 MB/s; a hot-swappable HDD tray to hot-swap the storage drive without turning off the system or dismantling the chassis; two mPCIe and one M.2 E key slots to install WiFi or 5G/ 4G wireless communication modules. The system is also equipped with 8x DIO, 2x COM ports, and dual display outputs for your industrial embedded application needs.

Nuvo-9531 series

Compact 8 fanless Box PC with Intel® Core™ i9/ i7/ i5/ i3 13th/12th Gen.

Nuvo-9531 series

SYSTEM

Processor	Supporting Intel® 13th-Gen Core™ CPU (LGA1700 socket, 65W/ 35W TDP) - Intel® Core™ i9-13900E/ i9-13900TE - Intel® Core™ i7-13700E/ i7-13700TE - Intel® Core™ i5-13500E/ i5-13400E/ i5-13500TE - Intel® Core™ i3-13100E/ i3-13100TE	Supporting Intel® 12th-Gen Core™ CPU (LGA1700 socket, 65W/ 35W TDP) - Intel® Core™ i9-12900E/ i9-12900TE - Intel® Core™ i7-12700E/ i7-12700TE - Intel® Core™ i5-12500E/ i5-12500TE - Intel® Core™ i3-12100E/ i3-12100TE - Intel® Pentium® G7400E/ G7400TE - Intel® Celeron® G6900E/ G6900TE
Chipset	Intel® H610E platform controller hub	
Graphics	Integrated Intel® UHD Graphics 770 (32EU) / 730 (24EU)	
Memory	Up to 32GB non-ECC DDR4 3200 SDRAM (one SODIMM slot)	
TPM	Supports dTPM 2.0	

I/O

Ethernet	4x 2.5GBASE-T Ethernet ports by Intel® I226-IT GbE controllers	
POE	Optional IEEE 802.3at PoE+ PSE for 4x2.5GbE ports 100 W total power budget	
USB	4x USB 3.2 Gen1 (5 Gbps) ports 2x USB 2.0 ports	
Video	1x VGA output, supporting 1920 x 1200 resolution 1x DisplayPort, supporting 4096 x 2304 resolution	
Serial port	1x software-programmable RS-232/422/485 ports (COM1) 3x 3-wire RS-232 ports (COM2/3/4) or 1x RS-422/485 port (COM2)	
Audio	1x 3.5 mm jack for mic-in and speaker-out	
Isolated DIO	4-CH isolated DI and 4-CH isolated DO	

EXPANSION BUS

Mini PCI Express	2x full-size mini PCI Express sockets with internal SIM sockets	
M.2	1x M.2 2230 E key socket for WiFi5, WiFi6 or Google edge TPU module	

STORAGE

SATA HDD	1x hot-swappable 2.5" HDD/ SSD tray for 7mm HDD/ SSD	
M.2	1x M.2 2280 M key socket (PCIe Gen4 x4) for NVMe SSD	

MECHANICAL

DC Input	1x 3-pin pluggable terminal block for 8 to 48V DC input with optional ignition power control	
Dimensions	212mm (W) x 165 mm (D) x 63 mm (H)	
Weight	2.5 kg	
Mounting	Wall-mount (standard) or DIN-rail mount (optional)	
Operating temperature	with 35W CPU: -25°C ~ 60°C * with 65W CPU (installation of the optional fan kit is recommended): -25°C ~ 60°C */**	
Storage temperature	-40°C ~ 85°C	
Humidity	10% ~ 90% non-condensing	
Vibration	MIL-STD-810H, Method 514.8, Category 4	
Shock	MIL-STD-810H, Method 516.8, Procedure I	
Certifications	CE/FCC Class A, according to EN 55032 & EN 55035	


*For sub-zero and over 60°C operating temperature, a wide temperature HDD or Solid State Disk (SSD) is required.

**For 65W CPUs, the optional fan kit is recommended for operating at ambient temperatures higher than 50°C.

Nuvo-9531 series

Compact 8 fanless Box PC with Intel® Core™ i9/ i7/ i5/ i3 13th/12th Gen.

Appearance and dimensions (mm)



Nuvo-9531 series

Compact 8 fanless Box PC with Intel® Core™ i9/ i7/ i5/ i3 13th/12th Gen.

Ordering information

Nuvo-9531 series	
MODEL NO.	
Nuvo-9531	Intel® 13th/12th-Gen Core™ i9/ i7/ i5/ i3 compact fanless computer with 4x 2.5GbE , 4x USB3.2 Gen 1 and a hot-swappable HDD tray
	Optional 802.3at PoE+ PSE for 4x 2.5GbE ports Optional ignition power control
OPTIONAL ACCESSORIES	
PA-160W-OW	160W AC-DC power adapter 20V/8A; 18AWG/120cm; cord end terminals for terminal block, operating temperature: -30°C to 70°C.
PA-280W-ET2	280W AC/DC power adapter 24V/ 11.67A ; 16AWG/ 100cm; cord end terminals for terminal block, operating temperature : -30°C to 60°C. (recommended for 65W CPU)
DINRAIL-31	DIN-rail mounting assembly for Nuvo-9531 series
Fan kit	Fan kit with 92mm x 92mm fan for Nuvo-9531 series