

OSPREY 21.5" Display

Industrial-grade 21.5" PCAP touch display

Features

- PCAP multi touch (resistive touch optional)
- LED backlight display (1.000 nits optional)
- Resolution: 1920 x 1080
- Video ports: VGA, DVI-I and HDMI
- Operating temperature: -5° ~ 50°C

Display	
Size	54.6cm (21.5") / 16:9 LED backlight
Touch Type	PCAP multi touch
Resolution	1920 x 1080 @ 60Hz
Colors	16.7M (8bits + FRC)
Active Display	476.6 (H) x 268.1 (V) mm
Pixel Pitch	0.248 (H) x 0.248 (V) mm
Contrast	1000:1
Brightness	250 nits (1.000 nits optional)
I/O	
USB	1x USB for touch screen
Video	1x VGA D-Sub 15-Pin optional: 1x DVI-I, 1x HDMI, S-Video, Composite
Power Input	1x DC input with external power adapter
Power Consumption	30 W typical, normal operation
OSD	
OSD Input	5x OSD keys
OSD Functions	Contrast, color, position, auto adjustment, factory settings

Front



Mechanical / Environmental	
Dimensions	542.5 x 334 x 46 mm (W x H x D)
Mounting	VESA mount kit (optional)
Temperature	Operation: -5° ~ 50°C / Storage: -30° to 70°C
Humidity	10 ~ 95%, non-condensing

Technical drawings

