

# OSS-PCIe-HIB25-x8

## PCIe x8 Gen 2 Host/Target Cable Adapter

### Features

- PCIe x8 Gen 2 HOST cable adapter installs in a x8, or x16 expansion slot of a host system. The TARGET adapter operates ONLY in the OSS 2-slot backplane to extend the PCIe bus to one additional PCIe slot.
- The HIB25-x8 cable adapter requires no additional software or drivers



### Specifications

Form Factor:	PCIe half-card
Operating Temperature:	0°C to +70°C environment
Storage Temperature:	-40°C to 85°C
Operating Humidity:	10% to 90% relative humidity non-condensing
Storage Humidity:	5% to 95% relative humidity non-condensing
Power:	4W
Connectors:	PCIe x8 cable connector PCIe x8 edge connector
Industry Specifications	PCIe External Cabling Specification, Rev. 1.0 PCI Express™ Card Electromechanical Specification, Rev. 2.0 PCI Express® Base Specification, Rev. 2.0 ATX Specification, Version 2.2
Re-drivers:	5.0 Gbps 4-Lane PCI Express Gen 2 Re-Driver with Equalization & Emphasis Pericom Part number PI2EQX5804
Bracket:	HIB2 x8 add-in card bracket Standard and low profile brackets No LEDs on bracket
Agency Compliance:	FCC Class B CE RoHS