# SENA Parani-MSP1000x - Series



## **Features**

- · Connects Bluetooth devices to 10/100 base-T Ethernet
- · Supports Bluetooth 2.0+EDR, up to 3Mbps throughput
- · 7/14/28 Bluetooth Connections support
- · Supports Bluetooth profiles for Serial Port, LAN Access, PAN, File Transfi and Dial up Networking.
- · Dual Ethernet support for fail-over operation
- · Ideal wireless solution for the replacement of the wired multi-port serial card.
- · Easy-to-use COM-Port redirector support, RFC 2217, Telnet COM Port Control Protocol
- · Flexible TCP/UDP host mode support: Multiple host connection/data transfer
- · Supports system logging & port logging
- Supports Python Script Engine for user customization
- Supports firmware upgrade via web, hyper terminal program or etc.

## Specifications

#### Ethernet Interface

- Dual 10/100 Base-T Ethernet with RJ45 connector Supports Static IP and Dynamic IP address

#### Bluetooth Interface

- Bluetooth v2.0 + EDR
- Class 1
- Profiles: Serial Port, LAN Access, PAN, Dial up Networking, File Transfer
- Data rate: up to 3Mbps
- Working distance Parani-MSP1000

	Parani-ESD110	
DAT-G01R Antenna	T-G01R Antenna	up
DAT-G01R Antenna	T-G01R Antenna	up
DAT-G01R Antenna	T5-G01R Antenna	up
DAT-G01R Antenna	AT-G01R Antenna	up
DAT5-G01R Antenna	T5-G01R Antenna	up
DAT5-G01R Antenna	AT-G01R Antenna	up
PAT-G01R Antenna	AT-G01R Antenna	up t

Parani-SD100

Max. Tx power: +17dBi(Using DAT-G01R Antenna)

Receive Sensitivity: -88dBm

# Point to multi point connectivity

- Up to 28 connections

## **Network Protocols**

- IPv4, ICMP, ARP, TCP, HTTP, telnet, TFTP
- SSH, HTTPS, SSL/TLS, DNS
- SCP/SFTP/FTP, syslog, NTP
- SMTP. Dynamic DNS

Security: IP Filtering, SSH v2, SSL/TLS, HTTPS, SCP, SFTP

CF Port: Flash memory

Logging: Syslog server, CF memory



Real Time Clock: Built-in support

#### Customization

- Python Script engine, ELDK v4.0, 2MB internal user space

#### Management

- Windows Utility
- Web, Telnet, Serial Console

#### Firmware Upgrade

- Telnet/SSH, Web, Bootp, CF memory, Zmodem, TFTP

#### Diagnostic LED

- POWER, STATUS, Ethernet0, Ethernet1
- Signal Strength, No of Connections

# Power

- Nominal Current Consumption: 1.2A@ 5VDC approximately

#### **Environmental**

- Operating temperature: 0°C to 50°C
- Storage temperature: -30°C to 85°C
- Humidity: 90% Non-condensing

## Physical properties

- Dimension(L x W x H): 203 x 170 x 44(mm)

7.99 x 6.69 x 1.73(in.)

- Weight:

MSP1000A: 1414g MSP1000B: 1432g MSP1000C: 1468g

MTBF: 30.52 Years

Certification: FCC. CE. TELEC

Warranty: 3-year limited warranty

# Ordering

MSP1000A Parani-MSP1000A Industrial Bluetooth Access Point with 7 connections support Parani-MSP1000B Industrial Bluetooth Access Point with 14 connections support MSP1000C Parani-MSP1000C Industrial Bluetooth Access Point with 28 connections support

## Includes

- DC Power Adapter
- DAT-G01R: 3 dBi Dipole Antenna RP-SMA Plug Right-hand Thread
- Serial data cable
- Ethernet straight cable
- Wall mount bracket
- Quick Start Guide

#### Optional Accessories

- DAT5-G01R: 5 dBi Dipole Antenna RP-SMA Plug Right-hand Thread
- PAT-G01R: 9dBi Patch Antenna with RP-SMA Plug Right hand Thread Default Cable. (SMA Jack Right hand Thread w/o Default Cable)
- SEC-G01R: 15cm Extension Cable(For SAT-G01R / DAT-G01R / DAT5-G01R)
- RFC-G01R: 1m Extension Cable(For PAT-G01R)